

AMENDMENTS TO THE CLAIMS

1. (Cancelled)

2. (Currently Amended) The liquid crystal display device according to claim [[1]]3, wherein the upper and lower orientation films are aligned parallel to each other.

3. (Currently Amended) ~~The liquid crystal display device according to claim 1, wherein the liquid crystal layer initially has an alignment state parallel to the upper and lower substrates adjacent to the upper and lower substrates; perpendicular to the upper and lower substrates at a midpoint between the upper and lower substrates; and tilted to the upper and lower substrates between the upper substrate and the midpoint and between the lower substrate and the midpoint.~~ A liquid crystal display device, comprising:

an upper substrate and a lower substrate facing and spaced apart from each other;

an upper orientation film on an inner surface of the upper substrate;

a lower orientation film on an inner surface of the lower substrate;

a liquid crystal layer interposed between the upper and lower orientation films;

an upper polarizing plate on an outer surface of the upper substrate;

a lower polarizing plate on an outer surface of the lower substrate; and

at least one compensation film disposed between the upper substrate and the upper polarizing plate;

wherein the compensation film is multi-layers of a first A-plate, an O-plate and a second A-plate.

4. (Cancelled)

5. (Currently amended) The liquid crystal display device according to claim [[4]]3, wherein a sum of retardations of the first and second A-plates is within a range of about 40 to 350 nanometers.

6. (Currently amended) The liquid crystal display device according to claim [[4]]3, wherein a retardation of the O-plate is within a range of about 40 to 350 nanometers.

7. (Currently amended) The liquid crystal display device according to claim [[4]]3 further comprising a plurality of C-plates in the compensation film.

8. (Original) The liquid crystal display device according to claim 7, wherein a sum of retardations of the C-plates is within a range of about 100 to 700 nanometers.

9. (Cancelled)

10. (Currently amended) The liquid crystal display device according to claim [[9]]3 wherein sum of retardations of the first and second A-plates with respect to x-y axis $d(n_x - n_y)$ is within a range of about 50 to 300 nanometers, and wherein sum of retardations of the first and second A-plates with respect to x-z axis $d(n_x - n_z)$ is within a range of about 100 to 700 nanometers.

11. (Currently Amended) The liquid crystal display device according to claim ~~[[1]]~~3, further comprising a plurality of C-plates in the compensation film.

12. (Original) The liquid crystal display device according to claim 11, wherein a sum of retardations of the C-plates is within a range of about 100 to 700 nanometers.

13. (Currently Amended) The liquid crystal display device according to claim ~~[[1]]~~3, wherein the compensation film is multi-layers of an A-plate and a splayed O-plate, optical axes of the splayed O-plate having a splayed structure.

14. (Cancelled)

15. (Currently Amended) The liquid crystal display device according to claim ~~[[14]]~~16, wherein the upper and lower orientation films are aligned parallel to each other.

16. (Currently Amended) ~~The liquid crystal display device according to claim 14, wherein the liquid crystal layer initially has an alignment state parallel to the upper and lower substrates adjacent to the upper and lower substrates; perpendicular to the upper and lower substrates at a midpoint between the upper and lower substrates; and tilted to the upper and lower substrates between the upper substrate and the midpoint and between the lower substrate and the midpoint.~~ A liquid crystal display device, comprising:

an upper substrate and a lower substrate facing and spaced apart from each other;

an upper orientation film on an inner surface of the upper substrate;

a lower orientation film on an inner surface of the lower substrate;

a liquid crystal layer interposed between the upper and lower orientation films;

an upper polarizing plate on an outer surface of the upper substrate;

a lower polarizing plate on an outer surface of the lower substrate; and

at least one compensation film disposed between the lower substrate and the lower

polarizing plate;

wherein the compensation film is multi-layers of a first A-plate, an O-plate and a second

A-plate.

17. (Cancelled)

18. (Currently amended) The liquid crystal display device according to claim [[17]]

16, wherein a sum of retardations of the first and second A-plates is within a range of about 40 to 350 nanometers.

19. (Currently amended) The liquid crystal display device according to claim [[17]]

16, wherein a retardation of the O-plate is within a range of about 40 to 350 nanometers.

20. (Currently amended) The liquid crystal display device according to claim [[17]]

16, further comprising a plurality of C-plates in the compensation film.

21. (Previously Presented) The liquid crystal display device according to claim 20,

wherein a sum of retardations of the C-plates is within a range of about 100 to 700 nanometers.

22. (Cancelled)

23. (Currently Amended) The liquid crystal display device according to claim [[14]] 16, wherein sum of retardations of the first and second A-plates with respect to x-y axis $d(n_x - n_y)$ is within a range of about 50 to 300 nanometers, and wherein sum of retardations of the first and second A-plates with respect to x-z axis $d(n_x - n_z)$ is within a range of about 100 to 700 nanometers.

24. (Currently Amended) The liquid crystal display device according to claim [[14]] 16, further comprising a plurality of C-plates in the compensation film.

25. (Original) The liquid crystal display device according to claim 24, wherein a sum of retardations of the C-plates is within a range of about 100 to 700 nanometers.

26. (Currently Amended) The liquid crystal display device according to claim [[14]] 16, wherein the compensation film is multi-layers of an A-plate and a splayed O-plate, optical axes of the splayed O-plate having a splayed structure.

27. (Previously Presented) A liquid crystal display device, comprising:
an upper substrate and a lower substrate facing and spaced apart from each other;
an upper orientation film on an inner surface of the upper substrate;
a lower orientation film on an inner surface of the lower substrate;
a liquid crystal layer interposed between the upper and lower orientation films;
an upper polarizing plate on an outer surface of the upper substrate;
a lower polarizing plate on an outer surface of the lower substrate; and

at least one compensation film disposed between the upper substrate and the upper polarizing plate,

wherein the compensation film is multi-layers of a first biaxial film, an O-plate and a second biaxial film, three dimensional refractive index of the first and second biaxial films having a relation of $n_x \neq n_y \neq n_z$.

28. (Previously Presented) A liquid crystal display device, comprising:

- an upper substrate and a lower substrate facing and spaced apart from each other;
- an upper orientation film on an inner surface of the upper substrate;
- a lower orientation film on an inner surface of the lower substrate;
- a liquid crystal layer interposed between the upper and lower orientation films;
- an upper polarizing plate on an outer surface of the upper substrate;
- a lower polarizing plate on an outer surface of the lower substrate; and
- at least one compensation film disposed between the lower substrate and the lower polarizing plate,

wherein the compensation film is multi-layers of a first biaxial film, an O-plate and a second biaxial film, three dimensional refractive index of the first and second biaxial films having a relation of $n_x \neq n_y \neq n_z$.